



US006517496B1

(12) **United States Patent**
Mault(10) **Patent No.:** **US 6,517,496 B1**
(45) **Date of Patent:** **Feb. 11, 2003**(54) **AIRWAY-BASED CARDIAC OUTPUT
MONITOR AND METHODS FOR USING
SAME**(75) **Inventor:** **James R. Mault**, Evergreen, CO (US)(73) **Assignee:** **HealtheTech, Inc.**, Golden, CO (US)(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.(21) **Appl. No.:** **09/674,899**(22) **PCT Filed:** **May 10, 2000**(86) **PCT No.:** **PCT/US00/12745**

§ 371 (c)(1),

(2), (4) **Date:** **Nov. 7, 2000**(87) **PCT Pub. No.:** **WO00/67634****PCT Pub. Date:** **Nov. 16, 2000****Related U.S. Application Data**(60) **Provisional application No.** 60/133,685, filed on May 10, 1999.(51) **Int. Cl.⁷** **A61B 5/08**(52) **U.S. Cl.** **600/532; 600/538; 600/529**(58) **Field of Search** **600/529-543, 600/526**(56) **References Cited****U.S. PATENT DOCUMENTS**

2,630,798 A	3/1953	White et al.
2,826,912 A	3/1958	Kritz
2,831,348 A	4/1958	Kritz
2,838,399 A	6/1958	Vogel, Jr.
2,869,357 A	11/1959	Kritz
2,911,825 A	11/1959	Kritz
2,920,012 A	1/1960	Sanders et al.

3,213,684 A	10/1965	Seaton et al.
3,220,255 A	11/1965	Scranton et al.
3,250,270 A	5/1966	Bloom
3,306,283 A	2/1967	Arp
3,523,529 A	8/1970	Kissen
3,527,205 A	9/1970	Jones
3,681,197 A	8/1972	Smith

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

DE	198 10 476	9/1998
EP	0459647 A2	12/1991
EP	0 712 638	12/1995
GB	2323292	9/1998
WO	WO 96/40340	12/1996


OTHER PUBLICATIONS

Medical Progress Through Technology, vol. 9, No. 1, 1982 Berlin (D), pp. 27-32, R. Salminen et al., "Computerized Breath-By-Breath Analysis of Respiratory Variables During Exercise."

(List continued on next page.)

Primary Examiner—Max Hindenburg*Assistant Examiner*—Navin Natnithithadha(74) *Attorney, Agent, or Firm*—Gifford, Krass, Groh, Sprinkle, Anderson & Citkowski, P.C.(57) **ABSTRACT**

A respiratory gas analyzer for measuring the cardiac output of a subject includes a flow meter and an oxygen sensor interconnected with one another between a mouthpiece and a source of respiratory gases, which may be a controlled source or the atmosphere. An oximeter provides measurements of the oxygen saturation of the subject. A computer connected to receive the signals from the flow meter, oxygen sensor, and oximeter can then calculate the subject's cardiac output.

22 Claims, 3 Drawing Sheets

U.S. PATENT DOCUMENTS

3,726,270 A 4/1973 Griffis et al.
 3,797,480 A 3/1974 Williams
 3,799,149 A 3/1974 Rummel et al.
 3,814,091 A 6/1974 Henkin
 3,834,375 A 9/1974 Sanctuary et al.
 3,895,630 A 7/1975 Bachman
 3,938,551 A 2/1976 Henkin
 3,962,917 A 6/1976 Terada
 4,003,396 A 1/1977 Fleischmann
 4,051,847 A 10/1977 Henkin
 4,078,554 A 3/1978 Lemaitre et al.
 4,186,735 A 2/1980 Henneman et al.
 4,188,946 A 2/1980 Watson et al.
 4,197,857 A 4/1980 Osborn
 4,200,094 A 4/1980 Gedeon et al.
 4,211,239 A 7/1980 Raemer et al.
 4,221,224 A 9/1980 Clark
 4,230,108 A 10/1980 Young
 4,341,867 A 7/1982 Johansen
 4,359,057 A 11/1982 Manzella
 4,368,740 A 1/1983 Binder
 4,386,604 A 6/1983 Hershey
 4,425,805 A 1/1984 Ogura et al.
 4,440,177 A 4/1984 Anderson et al.
 4,444,201 A 4/1984 Itoh
 4,463,764 A 8/1984 Anderson et al.
 4,572,208 A 2/1986 Cutler et al.
 4,598,700 A 7/1986 Tamm
 4,608,995 A 9/1986 Linnarsson et al.
 4,619,269 A 10/1986 Cutler et al.
 4,648,396 A 3/1987 Raemer
 4,658,832 A 4/1987 Brugnoli
 4,753,245 A 6/1988 Gedeon
 4,756,670 A 7/1988 Arai
 4,781,184 A 11/1988 Fife
 4,796,639 A 1/1989 Snow et al.
 4,850,371 A 7/1989 Broadhurst et al.
 4,856,531 A 8/1989 Merilainen
 4,909,259 A 3/1990 Tehrani
 4,914,959 A 4/1990 Mylvaganam et al.
 4,917,108 A 4/1990 Mault
 4,949,724 A 8/1990 Mahutte et al.
 4,955,946 A 9/1990 Mount et al.
 4,986,268 A 1/1991 Tehrani
 4,998,018 A 3/1991 Kurahashi et al.
 5,022,406 A 6/1991 Tomlinson
 5,038,773 A 8/1991 Norlien et al.
 5,038,792 A 8/1991 Mault
 5,042,500 A 8/1991 Norlien et al.
 5,042,501 A 8/1991 Kenny et al.
 5,060,506 A 10/1991 Douglas
 5,060,655 A 10/1991 Rudolph
 5,060,656 A 10/1991 Howard
 5,069,220 A 12/1991 Casparie et al.
 5,072,737 A 12/1991 Goulding
 5,081,871 A 1/1992 Glaser
 5,095,900 A 3/1992 Fertig et al.
 5,095,913 A 3/1992 Yelderman et al.
 5,117,674 A 6/1992 Howard
 5,119,825 A 6/1992 Huhn
 5,178,155 A 1/1993 Mault

5,179,958 A 1/1993 Mault
 5,214,966 A 6/1993 Delsing
 5,233,996 A 8/1993 Coleman et al.
 5,282,473 A 2/1994 Braig et al.
 5,285,794 A 2/1994 Lynch
 5,293,875 A 3/1994 Stone
 5,299,579 A 4/1994 Gedeon et al.
 5,303,712 A 4/1994 Van Duren
 5,309,921 A 5/1994 Kisner et al.
 5,326,973 A 7/1994 Eckerbom et al.
 5,355,879 A 10/1994 Brain
 5,355,893 A 10/1994 Mick et al.
 5,357,972 A 10/1994 Norlien
 5,363,857 A 11/1994 Howard
 5,398,695 A 3/1995 Anderson et al.
 5,402,796 A 4/1995 Packer et al.
 5,419,326 A 5/1995 Harnoncourt
 5,425,374 A 6/1995 Ueda et al.
 5,450,193 A 9/1995 Carlsen et al.
 5,468,961 A 11/1995 Gradon et al.
 5,503,151 A 4/1996 Harnoncourt et al.
 5,570,697 A 11/1996 Walker et al.
 5,632,281 A 5/1997 Rayburn
 5,645,071 A 7/1997 Harnoncourt et al.
 5,647,370 A 7/1997 Harnoncourt
 5,676,132 A 10/1997 Tillotson et al.
 5,705,735 A 1/1998 Acorn
 5,754,288 A 5/1998 Yamamoto et al.
 5,789,660 A 8/1998 Kofoed et al.
 5,796,009 A 8/1998 Delsing
 5,800,360 A 9/1998 Kisner et al.
 5,816,246 A 10/1998 Mirza
 5,831,175 A 11/1998 Fletcher-Haynes
 5,834,626 A 11/1998 DeCastro et al.
 5,836,300 A 11/1998 Mault
 5,922,610 A 7/1999 Alving et al.
 5,932,812 A 8/1999 Delsing
 5,957,858 A 9/1999 Micheels et al.
 6,010,459 A 1/2000 Silkoff et al.
 6,044,843 A 4/2000 O'Neil et al.
 6,162,180 A * 12/2000 Miesel et al. 600/481
 6,309,360 B1 * 10/2001 Mault 128/200.24

OTHER PUBLICATIONS

British Journal Of Anaesthesia, vol. 49, 1977 London (GB)
 pp. 575-587, J. A. Bushman et al. "Closed Circuit Anaes-
 thesia."

IEEE Transactions on Biomedical Engineering, vol. 35, No.
 9, Sep. 1988, pp. 653-659, Capek et al., "Noninvasive
 Measurement of Cardiac Output Using Partial CO₂
 ReBreathing."

Clinics in Chest Medicine (Review), vol. 10, 1989, pp.
 255-264, Heigenhauser et al., "Measurement of Cardiac
 Output by Carbon Dioxide Rebreathing Methods."

Determination Of Nitric Oxide Levels By Fluorescence
 Spectroscopy, Gabor G. and Allon, N. in Biochemical,
 Pharmacological, and Clinical Aspects of Nitric Oxide,
 edited by B. A. Weissman et al, Plenum Press, New York,
 1995, pp. 57.

* cited by examiner

FIG - 1




FIG - 2





FIG - 3

1

AIRWAY-BASED CARDIAC OUTPUT MONITOR AND METHODS FOR USING SAME

This application claims benefit of Ser. No. 60/133,685
filed May 10, 1999.

FIELD OF THE INVENTION

The present invention relates to measurement of cardiac
output of a patient. More specifically, the present invention
relates to an apparatus and method for non-invasive cardiac
output measurement of a subject utilizing a respiratory gas
analyzer employing a flow sensor, an oxygen sensor, and a
pulse oximeter which are interconnected to measure the
cardiac output of the subject.

BACKGROUND OF THE INVENTION

U.S. Pat. No. 5,836,300 to Applicant discloses a respira-
tory gas analyzer for measuring the metabolic activity and
the cardiac output of a subject including a bidirectional flow
meter and a capnometer sensor interconnected by conduits
and valving between a mouthpiece and a source of respira-
tory gases which can be a controlled source or the atmo-
sphere. A computer receiving signals from the flow meter
and the capnometer can then calculate the subject's meta-
bolic activity. When valving is shifted, a portion of the
exhaled gases are stored in the conduit so that upon in-
halation, the subject inhales a substantial portion of
rebreathed gases. The computer can then calculate the
patient's cardiac output as a function of the changes in total
carbon dioxide content of the exhaled gas before and after
the valve is shifted from a direct input to a rebreathed
position and the difference in end-tidal carbon dioxide
between the two positions.

The cardiac output of a patient, that is the volume of blood
ejected from the heart per unit time, is an important mea-
sured parameter in hospitalized patients. Currently, cardiac
output is routinely measured by invasive techniques includ-
ing thermal dilution using an indwelling pulmonary artery
catheter. This technique has several disadvantages including
the morbidity and mortality risks of placing an invasive
intracardiac catheter, the infectious disease risks, significant
expense and the fact that it provides an intermittent rather
than a continuous measurement. A noninvasive, reusable
cardiac output measurement device would substantially
improve patient care and reduce hospital costs.

The partial rebreathing technique mentioned above is a
known method for cardiac output measurement. As
described in Kapec and Roy, "The Noninvasive Measure-
ment of Cardiac Output Using Partial CO₂ Rebreathing,"
IEEE Transactions on Biomedical Engineering, Vol. 35, No.
9, September 1988, pp. 653-659, the method utilizes well
known Fick procedures, substituting carbon dioxide for
oxygen, and employing a sufficiently short measurement
period such that venous carbon dioxide levels and cardiac
output can be assumed to remain substantially constant
during the measurement.

U.S. Pat. No. 4,949,724 to Mahutte et al. discloses a
method and apparatus for continuously monitoring cardiac
output by utilizing a modified Fick equation. The Mahutte et
al. patent replaces VO₂ in the Fick equation by VCO₂
divided by a constant representative of the gas exchange
ratio of a patient in order to eliminate inaccuracies associ-
ated with monitoring the rate of uptake of oxygen.

2

In its original form, the Fick method of measuring cardiac
output requires blood gas values for arterial and mixed
venous blood as follows:

$$C.O. = \frac{VO_2}{CaO_2 - CvO_2}$$

where C.O. is cardiac output, VO₂ is oxygen consumption,
CaO₂ is the arterial oxygen content, and CvO₂ is the venous
oxygen content.

By utilizing a respiratory analyzer with a fast-response
oxygen sensor, the cardiac output can be determined based
on the end-tidal oxygen concentration (EtO₂). End-tidal
oxygen concentration is the lowest value of oxygen concen-
tration in breath. The end-tidal oxygen concentration
approximates the pulmonary capillary oxygen concentra-
tion.

Alternatively, at different points in time, it is also true that

$$C.O. = \frac{VO_{2(1)}}{CaO_{2(1)} - CvO_{2(1)}} = \frac{VO_{2(2)}}{CaO_{2(2)} - CvO_{2(2)}}$$

If the oxygen concentration of the inspired gas is tempo-
rarily increased or decreased, the change in alveolar oxygen
concentration will cause a transient uptake or release of
oxygen across the pulmonary capillaries, thereby resulting
in a change in the measured VO₂ and arterial oxygen content
(CaO₂). If these parameters are measured during an interval
of time less than the circulation time (i.e., less than approxi-
mately thirty-fifty seconds), then the venous oxygen content
(CvO₂) level remains essentially constant during this period
and can be removed from the equation. Therefore, cardiac
output can be determined based on the equation

$$C.O. = \frac{\Delta VO_2}{\Delta CaO_2}$$

The use of these novel concepts in combination with the
apparatus and method of the present invention therefore
allows for the non-invasive measurement of cardiac output
utilizing measurements of airway gases and arterial oxygen
concentrations, both of which can be done by non-invasive
techniques.

SUMMARY OF THE INVENTION

The present invention is accordingly directed toward an
airway-based respiratory gas analyzer for measuring the
cardiac output of a subject. In a preferred embodiment of the
analyzer of the present invention, the analyzer includes a
respiratory connector operative to be supported in contact
with a subject so as to pass inhaled and exhaled gases as the
subject breathes. A flow meter operatively connected to the
respiratory connector generates electrical signals as a func-
tion of the volume of gases which pass therethrough and, in
combination with the signals generated by an oxygen sensor,
allows for the determination of oxygen consumption (VO₂)
by integrating the flow and oxygen concentration signals
over an entire breath. The oxygen sensor can also provide for
the measurement of end-tidal (EtO₂) concentration. An
oximeter provides measurements of the subject's oxygen
saturation. A computation unit receives the output signals
from the flow sensor, oxygen sensor and oximeter and
calculates the cardiac output based on the generated signals.

An alternative mechanism for performing measurements
of the subject's cardiac output includes the subject placing

the mouthpiece of the analyzer into their mouth and breathing a first oxygen concentration for a first period of time. Typically, the source of respiratory gases is atmospheric air. As the subject breathes, oxygen consumption (VO_2) is determined as the integral of the flow and oxygen concentration signals over the entire breath. The oximeter provides a measurement of the subject's oxygen saturation which is utilized to calculate the subject's arterial oxygen content. After obtaining the measurement of the oxygen consumption (VO_2) and arterial oxygen content (CaO_2) over the first time period, the oxygen blender is caused to provide an increase or decrease in the airway oxygen concentration of the subject for a second period of time which is less than the subject's circulation time. The oxygen consumption (VO_2) and arterial oxygen content (CaO_2) are measured over this second time period on a breath-by-breath basis and are utilized in calculating the subject's cardiac output.

According to one aspect of the present invention, there is provided a respiratory gas analyzer for measuring cardiac output of a subject, said analyzer comprising:

- a respiratory connector operative to be supported in contact with a subject so as to pass inhaled and exhaled gases as the subject breathes;
- a flow sensor operatively connected to said respiratory connector adapted to generate electrical signals as a function of the volume of gases which pass there-through;
- an oxygen sensor for sensing the concentration of oxygen in the inhaled and exhaled gases, to thereby enable a determination to be made of the oxygen consumed by the subject during each breath;
- conduits interconnecting said respiratory connector, said flow meter, and said oxygen sensor;
- an oximeter for enabling a determination to be made of the concentration of oxygen in the subject's arterial blood; and
- a computer for receiving output signals from said flow sensor, said oxygen sensor, and said oximeter to calculate the cardiac output of the subject without the need for sensing the concentration of oxygen in the subject's venous blood.

According to one preferred embodiment of the invention described below, the analyzer is used in a two-measurement procedure, wherein the computer calculates the cardiac output (C.O.) of the subject according to the following equation:

$$C.O. = \frac{\Delta VO_2}{\Delta CaO_2}$$

wherein: ΔVO_2 is the difference in said consumed oxygen in the two-measurement procedure, and ΔCaO_2 is the difference in said arterial oxygen in the two-measurement procedure;

and wherein: the two-measurement procedure involves:

- (a) a first measurement of said consumed oxygen and said arterial oxygen during a first time interval, and
- (b) a second measurement, following a change in the oxygen content of the inhaled air, during a second time interval having a duration less than the blood circulation time of the subject.

According to a second described preferred embodiment, the computer calculates the cardiac output (C.O.) of the subject computer calculates the cardiac output (C.O.) of the subject according to the following equation:

$$C.O. = \frac{VO_2}{CaO_2 - CvO_2}$$

wherein: VO_2 is the oxygen consumed during a breath; CaO_2 is the concentration of oxygen in the subject's arterial blood; and CvO_2 is the concentration of oxygen in the subject's venous blood, which is assumed to be the same as the end-tidal oxygen concentration in the exhaled air.

Other features, advantages and applications of the present invention will be made apparent from the following detailed description of the preferred embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

Other advantages and applications of the present invention will be made apparent by the following detailed description of preferred embodiments of the invention. The description makes reference to the accompanying drawings in which:

FIG. 1 is a schematic representation of a first embodiment of the present invention;

FIG. 2 is a schematic representation of a second embodiment of the present invention; and

FIG. 3 is a graph of oxygen concentration over time measured in milliseconds to illustrate oxygen concentration as recorded with a fast-response oxygen sensor and is also illustrative end-tidal oxygen concentration.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1, a preferred embodiment of the present invention includes an airway-based cardiac output analyzer, generally indicated at 10, having a mouthpiece 12, a flow sensor 14, and a gas sensor 16. The flow sensor 14 and the gas sensor 16 are disposed in fluid communication with one another.

The mouthpiece 12 is adapted to engage the inner surfaces of a user's mouth, so as to form the sole passage for flowing respiratory gases into and out of the mouth. A nose clamp of conventional construction (not shown) can be employed in connection with the mouthpiece 12 to assure that all respiratory gas passes through the mouthpiece 12. In alternative configurations, a mask that engages the nose as well as the mouth of the user can be employed or an endotracheal tube could also be utilized.

The mouthpiece 12 is located adjacent to a bi-directional volume flow sensor 14. The flow sensor is preferably an ultrasonic flow meter such as an ultrasonic transit time flow meter such as that manufactured by NDD Medizintechnik AG, Zurich, Switzerland, and disclosed in U.S. Pat. Nos. 3,738,169; 4,425,805; 5,419,326; and 5,645,071. Preferably, the ultrasonic flow meter transmits and receives ultrasonic pulses along a path which is either parallel to or has a substantial component in the direction of the flow. The gas flow acts to advance or retard the flow of pulses so that the full transit time of the pulses is a function of the flow rate. Alternatively, the flow sensor 14 can be of the pressure differential type such as manufactured by Medical Graphics Corporation, St. Paul, Minn. under the trademark MEDGRAPHICS and of the general type illustrated in U.S. Pat. No. 5,038,773. Alternatively, other types of flow transducers such as pneumatics or spirometers could also be employed. The electrical output of the bi-directional flow sensor 14 is connected to a computation unit 20 through a conductive line 22.

5

The other end of the flow sensor 14 is connected to the gas sensor 16. The gas sensor 16 is preferably a fast-response (i.e. 50–80 millisecond response time), flow-through type oxygen sensor and is preferably of the fluorescent quench type as disclosed in U.S. Pat. Nos. 3,725,658; 5,517,313; and 5,632,958. The preferred embodiment can employ a sensor manufactured by Sensors for Medicine and Science, Inc., Germantown, Md. The electrical output of the gas sensor 16 is connected to the computation unit 20 through a conductive line 24. The computation unit 20 can include a source (not shown) for directing exciting radiation to a fluorescent coating disposed on the oxygen sensor 16 and sensing the resulting fluorescence intensity which is diminished as a function of the concentration of oxygen in the gas flowing over its surface to produce a direct measurement of oxygen concentration. The exciting radiation and fluorescent signal can be carried to the sensor 16 by an optical fiber (not shown).

A pulse oximeter 26 can be utilized to monitor oxygen saturation by pulse oximetry. The pulse oximeter 26 provides an output signal which is received by the computation unit 20 which is indicative of saturation percentage. The output signal of the pulse oximeter 26 is connected to the computational unit 20 through a conductive line 28. In a preferred embodiment, the pulse oximeter is preferably of the type manufactured by Datax-Ohlmeda, Louisville, Colo. Alternatively, for most healthy individuals, the pulse oximeter 26 can be omitted and the oxygen saturation can be assumed to be approximately 95–96%.

Utilizing the Fick equation, in combination with the airway-based respiratory gas analyzer 10 having the flow sensor 14 and the fast-response oxygen sensor 16, allows for the determination of a subject's cardiac output by utilizing measurements of end-tidal oxygen concentration and VO_2 . The airway-based gas analyzer 10 allows for the determination of end-tidal oxygen concentration (EtO_2) as illustrated in FIG. 3. If one assumes that $EtO_2 \approx PvO_2$ (dissolved venous oxygen concentration in the plasma), then using the PvO_2 and the hemoglobin concentration, the SvO_2 can be determined based on the oxygen dissociation curve. The pulse oximeter 26 can be used to obtain oxygen saturation movement so that based on the Fick equation of

$$C.O. = \frac{VO_2}{CaO_2 - CvO_2}$$

wherein VO_2 is measured by the airway based respiratory analyzer, CaO_2 and CvO_2 are determined according to the equations

$$CaO_2 = [(SaO_2)(Hgb)(1.36) + (PaO_2)(0.0031)] \text{ and}$$

$$CvO_2 = [(SvO_2)(Hgb)(1.36) + (PvO_2)(0.0031)], \text{ respectively,}$$

wherein SaO_2 is the oxygen saturation measurement obtained by pulse oximetry, Hgb is the hemoglobin concentration (which is entered as a known value or by direct measurement), and PvO_2 is obtained from the measurement of EtO_2 . It is assumed that EtO_2 approximates PvO_2 and, if the PvO_2 and the hemoglobin concentrations are known, using the oxygen dissociation curve, SvO_2 can be determined. The pulse oximeter 26 measures SaO_2 (alternatively, SaO_2 and PaO_2 can be reasonably assumed).

Referring to FIG. 2, in an alternative embodiment of the present invention is shown wherein like numerals represent like elements among the embodiments, a gas blender 18 is disposed directly adjacent to and in fluid communication

6

with the gas sensor 16. The gas blender 18 is also in fluid communication with the atmosphere or a source and sink of respiratory gases. The gas blender 18 can also be connected to a ventilator or source of calibrated or known gases such as an external oxygen tank 30. The gas blender 18 is preferably computer controlled and is in electrical communication with the computation unit 20 through a conductive line 32. That is, the computation unit 20 can transmit signals to the gas blender 18 in order to modify, mix, or change the composition of the inhaled air passing through the cardiac output analyzer 10 to the subject. In other words, the gas blender 18 can be caused to allow an increase/decrease in the concentration of airway oxygen for a given or predetermined period of time.

In a further alternative embodiment, the pulse oximeter 26 can be replaced by a synchronized, side-port sampling oxygen sensor as is well known in the art. That is, a portion or sample of the gases flowing through the analyzer is directed via a port to an oxygen sensor.

The analyzer 10 can also incorporate an artificial nose and/or a bacterial filter as described in Applicant's previous patents or can incorporate a temperature sensor which provides a signal to the computation unit 20 to adjust the measurements as a function of breath and external air temperature.

In operation, in order to non-invasively obtain a measurement of the cardiac output of a subject, the subject attaches the pulse oximeter 22 to a suitable portion of their body such as a finger or earlobe, the subject then places the mouthpiece 12 into their mouth and the oxygen consumption (VO_2) is determined as the integral of the flow of oxygen concentration signals over an entire breath. The arterial oxygen concentration is calculated according to the formula:

$$CaO_2 = (SaO_2)(Hgb)(1.36) + (PaO_2)(0.0031)$$

where SaO_2 is the oxygen saturation measurement obtained by the pulse oximeter 22, Hgb is the hemoglobin concentration (which is entered as a known value or obtained by direct measurement), and PaO_2 is the dissolved arterial oxygen concentration. After obtaining a stable measurement of VO_2 and CaO_2 over a first time period of approximately two to three minutes, the gas blender 18 is caused to increase/decrease the concentration of oxygen (preferably, at least a 10% change in FIO_2 , e.g., 40% increased to 50%) supplied to the subject for a second time period less than the subject's circulation time of approximately thirty to fifty seconds. VO_2 and CaO_2 are monitored on a breath-by-breath basis during this time period and the cardiac output is then determined. Accordingly, the method and apparatus of the present invention take advantage of the phenomenon that if the oxygen concentration of the inspired gas is temporarily increased or decreased, the change in alveolar oxygen concentration will cause a transient uptake or release of oxygen across the pulmonary capillaries thereby resulting in a change in the measured VO_2 and arterial oxygen content (CaO_2). If these parameters are measured during an interval less than the circulation time (i.e., less than approximately thirty to fifty seconds), then the venous oxygen content (CvO_2) can be ignored and the cardiac output of the subject can be calculated based on the equation

$$C.O. = \frac{\Delta VO_2}{\Delta CaO_2}$$

In view of the teaching presented herein, other modifications and variations of the present invention will readily be

apparent to those of skill in the art. The discussion and description are illustrative of some embodiments of the present invention, but are not meant to be limitations on the practice thereof. It is the following claims, including all equivalents, which defines the scope of the invention.

What is claimed is:

1. A respiratory gas analyzer for measuring cardiac output of a subject, said analyzer comprising:

a respiratory connector operative to be supported in contact with a subject so as to pass inhaled and exhaled gases as the subject breathes;

a flow sensor operatively connected to said respiratory connector adapted to generate electrical signals as a function of the volume of gases which pass there-through;

an oxygen sensor for sensing the concentration of oxygen in the exhaled gases;

means for determining the concentration of oxygen in the inhaled gases and generating a signal representative of the oxygen consumed by the subject during each breath;

conduits interconnecting said respiratory connector, said flow meter, and said oxygen sensor;

an oximeter for enabling a determination to be made of the concentration of oxygen in the subject's arterial blood; and

a computer for receiving output signals from said flow sensor, said signal representative of the oxygen consumed by the subject during each breath, and said oximeter to calculate the cardiac output of the subject without the need for sensing the concentration of oxygen in the subject's venous blood.

2. The analyzer of claim 1, wherein, in a two-measurement procedure, said computer calculates the cardiac output (C.O.) of the subject according to the following equation:

$$C.O. = \frac{\Delta VO_2}{\Delta CaO_2}$$

wherein: ΔVO_2 is the difference in said consumed oxygen in the two-measurement procedure, and ΔCaO_2 is the difference in said arterial oxygen in the two-measurement procedure;

and wherein: the two-measurement procedure involves:

- (a) a first measurement of said consumed oxygen and said arterial oxygen during a first time interval, and
- (b) a second measurement, following a change in the oxygen content of the inhaled air, during a second time interval having a duration less than the blood circulation time of the subject.

3. The analyzer of claim 2, wherein said computer calculates the cardiac output (C.O.) of the subject according to the following equation:

$$C.O. = \frac{VO_2}{CaO_2 - CvO_2}$$

wherein: VO_2 is the oxygen consumed during a breath; CaO_2 is the concentration of oxygen in the subject's arterial blood; and CvO_2 is the concentration of oxygen in the subject's venous blood, which is assumed to be the same as the end-tidal oxygen concentration in the exhaled air.

4. The analyzer of claim 1 further including a gas blender operatively connected in fluid communication with said conduits for changing the concentration of the oxygen in the inhaled gases.

5. The analyzer of claim 1, wherein said oxygen sensor is a fluorescence quench oxygen sensor.

6. The analyzer of claim 1, wherein said oxygen sensor is a side-port sampling oxygen sensor.

7. The analyzer of claim 1, wherein said respiratory connector is a mouthpiece.

8. The analyzer of claim 4, wherein said flow sensor, said oxygen sensor, said oximeter, and said gas blender comprise a mechanism for transferring output signals therefrom to said computer.

9. The analyzer of claim 8, wherein said mechanism comprises a conductive line.

10. The analyzer of claim 4, wherein said gas blender is operatively connected to a source of respiratory gas.

11. The analyzer of claim 10, wherein said source of respiratory gas is the atmosphere.

12. The analyzer of claim 10, wherein said source of respiratory gas is a source of oxygen.

13. A method for non-invasive cardiac output measurement of a subject, said method comprising the steps of:

- (a) determining oxygen consumption of a subject;
- (b) determining end-tidal oxygen concentration of the subject; and
- (c) calculating the cardiac output of the subject based on the oxygen consumption and the end-tidal oxygen concentration determined in steps (a) and (b).

14. The method of claim 13, wherein the cardiac output (C.O.) is calculated according to the following equation:

$$C.O. = \frac{VO_2}{CaO_2 - CvO_2}$$

wherein: VO_2 is the oxygen consumed during a breath; CaO_2 is the concentration of oxygen in the subject's arterial blood; and CvO_2 is the concentration of the oxygen in the subject's venous blood and is determined in accordance with the equation

$$CvO_2 = (SvO_2)(Hbg)(1.36) + (0.0031)(PvO_2)$$

wherein SvO_2 is the oxygen saturation, Hbg is the hemoglobin concentration, and PvO_2 is the dissolved venous plasma oxygen and is assumed to be the determined end-tidal oxygen concentration of the subject.

15. The method of claim 14, wherein arterial oxygen content is determined in accordance with the equation

$$CaO_2 = (SaO_2)(Hbg)(1.36) + (0.0031)(PaO_2)$$

wherein SaO_2 is the arterial oxygen saturation, Hbg is the hemoglobin concentration, and PaO_2 is the dissolved arterial oxygen concentration.

16. A method for non-invasive cardiac output measurement of a subject, said method comprising the steps of:

- (a) determining oxygen consumption and arterial oxygen content of a subject over a first time interval and for a first oxygen concentration;
- (b) changing the oxygen concentration breathed by the subject for a second time interval wherein the second time interval is less than the circulation time of the subject; and
- (c) calculating the cardiac output of the subject based on the relative change in both oxygen consumption and arterial oxygen content determined in steps (a) and (b).

9

17. The method of claim 16, wherein the cardiac output (C.O.) of the subject is calculated according to the following equation:

$$C.O. = \frac{\Delta VO_2}{\Delta CaO_2}$$

wherein ΔVO_2 is said relative change in oxygen consumption and ΔCaO_2 is said relative change in arterial oxygen.

18. The method of claim 16, wherein said first time interval ranges from approximately one to five minutes.

10

19. The method of claim 18, wherein said first time interval ranges from approximately two to three minutes.

20. The method of claim 16, wherein said second time interval ranges from approximately twenty seconds to sixty seconds.

21. The method of claim 20, wherein said second time interval ranges from approximately thirty seconds to fifty seconds.

22. The method of claim 16, wherein the oxygen concentration in step (b) is increased from approximately 40 percent to approximately 50 percent.

* * * * *